

16500 - 16517

Shark Industries, Ltd. Paint Markers

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 04/16/2015
Revision date: 11/06/2015
Supersedes: 10/29/2015
Version: 1.2



Shark Industries, Ltd.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Trade name : Shark Industries, Ltd. Paint Markers
Synonyms : Shark Industries, Ltd. Paint Marker White, Yellow, Black, Blue, Green, Aluminum, Purple, Light Blue, Light Green, Fluorescent Yellow, Fluorescent Green, Fluorescent Orange, Fluorescent Pink, Invisible UV, Red, Orange, Pink, Brown, Gold
Shark Industries, Ltd. Paint Marker White, Yellow, Red, Black

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.

1.3. Details of the supplier of the safety data sheet

Shark Industries, Ltd.
6700 Bleck Drive
Rockford, MN 55373
Phone: (763) 565-1900
Fax: (763) 565-1991
E-mail: info@sharkind.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

2.4. Unknown acute toxicity (GHS US)

0.28 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
0.28 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
0.28 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
1-Methoxy-2-propanol N/A	(CAS No) 107-98-2	47.05 White 53.32 Yellow 56.66 Red 53.03 Black, CERTIFIED Black 55.56 Blue 56.4 Green 53.86 Orange 77.11 Aluminum 50.88 Purple 47.11 Pink 47.57 Light Blue 47.1 Light Green 56.53 Brown 71.2 Gold 42.53 Fluorescent Yellow, Fluorescent Orange 43.05 Fluorescent Green 42.29 Fluorescent Pink 50 Invisible UV 48.35 CERTIFIED White 53.71 CERTIFIED Yellow 56.8 CERTIFIED Red	Flam. Liq. 3, H226 STOT SE 3, H336
ethanol N/A	(CAS No) 64-17-5	13.07 White, CERTIFIED White 15.49 Yellow, CERTIFIED Yellow 13.47 Red, CERTIFIED Red 19.8 Black, CERTIFIED Black 14.18 Blue 12.89 Green 13.18 Orange, Brown 16.3 Purple 12.68 Pink 12.64 Light Blue 12.61 Light Green 8.04 Fluorescent Yellow, Fluorescent Orange 6.8 Fluorescent Green	Flam. Liq. 2, H225
2-methoxy-1-methylethyl acetate N/A	(CAS No) 108-65-6	0.3 – 0.6 White, CERTIFIED White 0.36 – 0.73 Yellow, CERTIFIED Yellow 0.47 – 0.94 Red, CERTIFIED Red 0.55 – 1.1 Black, CERTIFIED Black 0.76 – 1.52 Blue 0.74 – 1.48 Green 0.86 – 1.72 Orange 0.05 – 0.1 Purple 0.4 – 0.8 Pink 0.42 – 0.85 Light Blue 0.48 – 0.96 Light Green 0.6 – 1.21 Brown 0.97 – 1.93 Gold 0.21 – 0.41 Fluorescent Yellow, Fluorescent Orange, Fluorescent Pink 0.22 – 0.45 Fluorescent Green	Flam. Liq. 3, H226
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7	3.64 Red, CERTIFIED Red 0.89 Pink 1.82 Brown 1.22 Gold	Skin Sens. 1, H317
Isopropanol N/A	(CAS No) 67-63-0	2.31 White, CERTIFIED White 2.73 Yellow, CERTIFIED Yellow 2.38 Red, CERTIFIED Red 3.49 Black, CERTIFIED Black 2.5 Blue 2.28 Green 2.33 Orange, Brown 2.88 Purple 2.24 Pink 2.23 Light Blue, Light Green 1.42 Fluorescent Yellow, Fluorescent Orange 1.2 Fluorescent Green 1.49 Fluorescent Pink 0.54 Invisible UV	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



Name	Product identifier	% (w/w)	GHS-US classification
Ethyl acetate NA	(CAS No) 141-78-6	0.76 White, CERTIFIED White 0.91 Yellow, Red, CERTIFIED Yellow, CERTIFIED Red 0.93 Black, CERTIFIED Black 0.83 Blue 0.87 Green 0.89 Orange, Brown 0.79 Aluminum 1.1 Purple 0.73 Pink, Light Blue, Light Green 0.64 Gold 0.65 Fluorescent Yellow, Fluorescent Orange, Fluorescent Pink 0.7 Fluorescent Green 2.22 Invisible UV	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Carbon black C	(CAS No) 1333-86-4	1.84 Black, CERTIFIED Black	Carc. 2, H351
4-Methyl-7-diethylaminocoumarin NA	(CAS No) 91-44-1	1.43 Invisible UV	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
propyl acetate NA	(CAS No) 109-60-4	0.77 White, Orange, Brown, CERTIFIED White 0.91 Yellow, CERTIFIED Yellow 0.79 Red, CERTIFIED Red 1.16 Black, CERTIFIED Black 0.83 Blue 0.76 Green 0.96 Purple 0.75 Pink 0.74 Light Blue, Light Green 0.47 Fluorescent Yellow, Fluorescent Orange 0.4 Fluorescent Green 0.18 Invisible UV	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : May cause moderate irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Inert gas. Foam. Water spray. Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour. Burning produces irritating, toxic and noxious fumes.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses. Eliminate all ignition sources if safe to do so.

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.

Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Eliminate all ignition sources. Stop the flow of material, if this is without risk.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible products : Strong oxidizers.

Incompatible materials : Heat sources.

Heat and ignition sources : Keep away from heat, sparks and flame.

Prohibitions on mixed storage : Keep away from incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Valve Action® Paint Markers, CERTIFIED Valve Action® Paint Markers

ACGIH	Not applicable
OSHA	Not applicable

1-Methoxy-2-propanol (107-98-2)

ACGIH	ACGIH TWA (mg/m³)	369 mg/m³
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (mg/m³)	553 mg/m³
ACGIH	ACGIH STEL (ppm)	100 ppm

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



1-Methoxy-2-propanol (107-98-2)

ACGIH	Remark (ACGIH)	Eye irr; CNS impair; A4
OSHA	Not applicable	
Canada (Quebec)	VECD (mg/m ³)	553 mg/m ³
Canada (Quebec)	VECD (ppm)	150 ppm
Canada (Quebec)	VEMP (mg/m ³)	369 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm

Ethyl acetate (141-78-6)

ACGIH	ACGIH TWA (mg/m ³)	1440 mg/m ³
ACGIH	ACGIH TWA (ppm)	400 ppm
ACGIH	Remark (ACGIH)	URT & eye irr
OSHA	OSHA PEL (TWA) (mg/m ³)	1400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Canada (Quebec)	VEMP (mg/m ³)	1440 mg/m ³
Canada (Quebec)	VEMP (ppm)	400 ppm

2-methoxy-1-methylethyl acetate (108-65-6)

ACGIH	Not applicable	
OSHA	Not applicable	

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

ACGIH	Not applicable	
OSHA	Not applicable	

ethanol (64-17-5)

ACGIH	ACGIH TWA (mg/m ³)	1884 mg/m ³
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm
ACGIH	Remark (ACGIH)	URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Canada (Quebec)	VEMP (mg/m ³)	1880 mg/m ³
Canada (Quebec)	VEMP (ppm)	1000 ppm

Isopropanol (67-63-0)

ACGIH	ACGIH TWA (mg/m ³)	490 mg/m ³
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (mg/m ³)	960 mg/m ³
ACGIH	ACGIH STEL (ppm)	400 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Canada (Quebec)	VECD (mg/m ³)	1230 mg/m ³
Canada (Quebec)	VECD (ppm)	500 ppm
Canada (Quebec)	VEMP (mg/m ³)	983 mg/m ³
Canada (Quebec)	VEMP (ppm)	400 ppm

propyl acetate (109-60-4)

ACGIH	ACGIH TWA (mg/m ³)	835 mg/m ³
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (mg/m ³)	1040 mg/m ³
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



propyl acetate (109-60-4)		
OSHA	OSHA PEL (TWA) (mg/m ³)	840 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Canada (Quebec)	VECD (mg/m ³)	1040 mg/m ³
Canada (Quebec)	VECD (ppm)	250 ppm
Canada (Quebec)	VEMP (mg/m ³)	835 mg/m ³
Canada (Quebec)	VEMP (ppm)	200 ppm
Carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3.5 mg/m ³
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
Canada (Quebec)	VEMP (mg/m ³)	10 mg/m ³ (Fibres de carbone et de graphite; Poussière totale) 5 mg/m ³ (Fibres de carbone et de graphite; Poussière respirable) 3.5 mg/m ³
4-Methyl-7-diethylaminocoumarin (91-44-1)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls	: Provide local exhaust ventilation of closed transfer systems to minimize exposures.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: None under normal use. It is a good industrial hygiene practice to minimize skin contact. Wear suitable gloves, rubber.
Eye protection	: No special eye protection equipment recommended under normal conditions of use. Eye protection should only be necessary where liquid could be splashed or sprayed.
Respiratory protection	: No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of inadequate ventilation wear respiratory protection. Use an approved respirator equipped with oil/mist cartridges.
Consumer exposure controls	: Keep out of reach of children.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Variable.
Odour	: Solvent.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: < 1
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 120 °C
Flash point	: 31 °C
Auto-ignition temperature	: 287 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 11.8
Relative vapour density at 20 °C	: No data available
Relative density	: 1 - 1.33
Solubility	: insoluble in water.
Log Pow	: 0.7
Log Kow	: No data available
Viscosity, kinematic	: No data available

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 50 - 60 %
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Flammable liquid and vapour.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May release flammable gases. Burning produces irritating, toxic and noxious fumes. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1-Methoxy-2-propanol (107-98-2)

LD50 oral rat	4016 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 inhalation rat (ppm)	> 7000 ppm 6 hr
ATE CLP (oral)	4016.000 mg/kg bodyweight

Ethyl acetate (141-78-6)

LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	> 18 mg/l/4h
ATE CLP (oral)	5620.000 mg/kg bodyweight

2-methoxy-1-methylethyl acetate (108-65-6)

LD50 oral rat	8532 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (ppm)	4345 ppm 6 h
ATE CLP (oral)	8532.000 mg/kg bodyweight

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m ³ 4 h

ethanol (64-17-5)

LD50 oral rat	10470 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	133.8 mg/l/4h
ATE CLP (oral)	10470.000 mg/kg bodyweight
ATE CLP (vapours)	133.800 mg/l/4h
ATE CLP (dust,mist)	133.800 mg/l/4h

Isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	16.4 ml/kg
LC50 inhalation rat (ppm)	> 10000 ppm/4h
ATE CLP (oral)	5840.000 mg/kg bodyweight

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



propyl acetate (109-60-4)	
LD50 oral rat	8700 mg/kg
LD50 dermal rabbit	> 17800 mg/kg
LC50 inhalation rat (mg/l)	32 mg/l/4h
ATE CLP (oral)	8700.000 mg/kg bodyweight
ATE CLP (vapours)	32.000 mg/l/4h
ATE CLP (dust,mist)	32.000 mg/l/4h
Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m ³ 4 h
4-Methyl-7-diethylaminocoumarin (91-44-1)	
LD50 oral rat	> 5000 mg/kg
ATE CLP (dermal)	1100.000 mg/kg bodyweight
ATE CLP (dust,mist)	1,500 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.

Isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust
National Toxicology Program (NTP) Status	Not listed in carcinogenicity class

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified.
Specific target organ toxicity (repeated exposure)	: Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms

Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May cause moderate irritation.

SECTION 12: Ecological information

12.1 Toxicity

1-Methoxy-2-propanol (107-98-2)	
LC50 fish 1	20800 mg/l
EC50 Daphnia 1	23300 mg/l
ErC50 (algae)	> 1000 mg/l
Ethyl acetate (141-78-6)	
LC50 fish 1	220 mg/l
EC50 Daphnia 1	1200 mg/l
NOEC chronic fish	< 9.35 mg/l
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 fish 1	100 - 180 mg/l
EC50 Daphnia 1	> 500 mg/l 48 h
ErC50 (algae)	> 1000 mg/l
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h
ethanol (64-17-5)	
LC50 fish 1	14200 mg/l
EC50 Daphnia 1	5012 mg/l

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



Isopropanol (67-63-0)	
LC50 fish 1	10000 mg/l
propyl acetate (109-60-4)	
LC50 fish 1	60 mg/l 96 h
EC50 Daphnia 1	91.5 mg/l 48 h

12.2. Persistence and degradability

1-Methoxy-2-propanol (107-98-2)	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % 28 d
Ethyl acetate (141-78-6)	
Persistence and degradability	Readily biodegradable.
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Readily biodegradable.
Biodegradation	89 % 10 d
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d
ethanol (64-17-5)	
Biodegradation	> 96 % 28 d
Isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable.
propyl acetate (109-60-4)	
Persistence and degradability	Readily biodegradable.
Biodegradation	62 % 5 d
Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Valve Action® Paint Markers, CERTIFIED Valve Action® Paint Markers	
Log Pow	0.7
1-Methoxy-2-propanol (107-98-2)	
Bioaccumulative potential	Not expected to bioaccumulate.
Ethyl acetate (141-78-6)	
Bioaccumulative potential	Not expected to bioaccumulate.
2-methoxy-1-methylethyl acetate (108-65-6)	
Log Pow	0.43
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
BCF fish 1	53 l/kg
Log Pow	1.28
ethanol (64-17-5)	
Bioaccumulative potential	Not expected to bioaccumulate.
Isopropanol (67-63-0)	
Bioaccumulative potential	Not expected to bioaccumulate.
propyl acetate (109-60-4)	
Log Pow	1.23

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

In accordance with DOT and TDG

Transport document description	: UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base
Transport hazard class(es) (DOT)	: 3 - Flammable liquid
Packing group (DOT)	: III - Minor Danger

ADR

Transport document description	: UN 1263 PAINT, 3, III, (D/E)
Proper Shipping Name (ADR)	: PAINT
Packing group (ADR)	: III
Transport hazard class(es) (ADR)	: 3

Transport by sea

UN-No. (IMDG)	: UN 1263
Proper Shipping Name (IMDG)	: PAINT
Transport hazard class(es) (IMDG)	: 3
Packing group (IMDG)	: III

Air transport

UN-No. (IATA)	: UN 1263
Proper Shipping Name (IATA)	: Paint
Transport hazard class(es) (IATA)	: 3
Packing group (IATA)	: III

SECTION 15: Regulatory information

15.1. US Federal regulations

1-Methoxy-2-propanol (107-98-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethyl acetate (141-78-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
--	---------

2-methoxy-1-methylethyl acetate (108-65-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Isopropanol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Fire hazard
-------------------------------------	-------------

propyl acetate (109-60-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-Methyl-7-diethylaminocoumarin (91-44-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



15.2. International regulations

CANADA

1-Methoxy-2-propanol (107-98-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Ethyl acetate (141-78-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2-methoxy-1-methylethyl acetate (108-65-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

propyl acetate (109-60-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

4-Methyl-7-diethylaminocoumarin (91-44-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

1-Methoxy-2-propanol (107-98-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethyl acetate (141-78-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2-methoxy-1-methylethyl acetate (108-65-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

ethanol (64-17-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Isopropanol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

propyl acetate (109-60-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4-Methyl-7-diethylaminocoumarin (91-44-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Valve Action® Paint Markers, CERTIFIED Valve Action® Paint Markers

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

15.3. US State regulations

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



Valve Action® Paint Markers, CERTIFIED Valve Action® Paint Markers

State or local regulations	The carbon black in this product is bound and is not respirable. California Prop. 65 warnings are not required.
----------------------------	---

Carbon black (1333-86-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

1-Methoxy-2-propanol (107-98-2)

U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Right to Know List of Hazardous Chemicals

Ethyl acetate (141-78-6)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - List of Hazardous Substances

ethanol (64-17-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

Isopropanol (67-63-0)

U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List

propyl acetate (109-60-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

Carbon black (1333-86-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes	: Added. Product.
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .
Abbreviations and acronyms	: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CLP: Classification, Labelling, Packaging. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. PBT: Persistent, Bioaccumulative, Toxic. TWA: Time Weight Average. TSCA: Toxic Substances Control Act.
Other information	: None.

Shark Industries, Ltd. Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)



NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Full text of H-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer

SDS Prepared by: Shark Industries, Ltd.
6700 Bleck Drive
Rockford, MN 55373
P: (763) 565-1900
www.sharkind.com

Shark Industries, Ltd. NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

